



**FREQUENCY CONVERTER SPECIFICATION**  
**GEORATOR CORPORATION**  
 MANASSAS, VIRGINIA 20110

Model No. 30-103  
 Type 51-A Unit Shell Frequency Converter

**1.0 INPUT:**

- 1.1 Motor: Stator & Rotor; 2-1/4 HP, 3 Phase, 50 Hz, 220/380V, 2900 RPM Full Load, Induction Motor, Georator P/N 18-210.
- 1.2 Input Current: 7/4 Amperes
- 1.3 Insulation: Class B
- 1.4 Max. Ambient Temperature: 50 Degrees C
- 1.5 Duty: Continuous

**2.0 OUTPUT:**

- 2.1 Rating: 1.5 KVA, 100% PF, 3 Phase, 400 Hz (Nom.), 115/200V Or 115V (Nom.).
- 2.2 Output Voltage, No Load: Approximately 124V L-N
- 2.3 Output Current: 7.5/4.4 Amperes
- 2.4 Insulation: Class B
- 2.5 Max. Ambient Temperature: 50 Degrees C
- 2.6 Dielectric Strength, Winding To Frame: 1500V For 1 Minute

**3.0 VIBRATION: Within 0.001**

**4.0 BEARINGS: Shielded Life Time Lubricated**

**5.0 FINISH:**

- 5.1 Primer: Iridite
- 5.2 Paint: Silver-Blue Enamel
- 5.3 Fasteners: Zinc Plated

**6.0 APPROXIMATE WEIGHT:**

- 6.1 Net: 117 Lbs.
- 6.2 Shipping: 145 Lbs.

Revision Letter	Date	Revision Description
ENGINEER		M.T.E.
APPROVED BY		April 20, 1998



**GEORATOR SPECIFICATION**  
**GEORATOR CORPORATION**  
MANASSAS, VIRGINIA 20110