



FREQUENCY CONVERTER SPECIFICATION
GEORATOR CORPORATION
 MANASSAS, VIRGINIA 20110

Model No. 33-049

Type 33-A Vertical Converter

1.0 INPUT:

- 1.1 Motor, Rotor & Stator: Reliance, Frame 254T, Georator P/N 18-484: 220/380V, 6 Leads, 12 H.P., 3 Phase, 50 Hz., 1450 RPM (Nom.)
- 1.2 Input Current: 33.6/19.4 Amperes
- 1.3 Insulation: Class B
- 1.4 Temperature Rise: 55 Degree C
- 1.5 Duty: Continuous
- 1.6 Dielectric Strength, Winding to Frame: 1880V for 1 Minute

2.0 OUTPUT:

- 2.1 Rating: 7.5 KVA, 100% PF, 3 Phase, 400 Hz (Nom.), 115/200V or 115V (Nom.)
- 2.2 Output Voltage, No Load: 124V +-1V L-N
- 2.3 Output Frequency Tolerances: 400 Hz No Load to 388 Hz Min. at Full Load
- 2.4 Output Current: 38/22 Amperes
- 2.5 Temperature Rise: 40 Degree C
- 2.6 Duty: Continuous
- 2.7 Dielectric Strength, Winding to Frame: 1500V for 1 Minute

3.0 VIBRATION: Within 0.0015

4.0 BEARINGS: Shielded Life Time Lubricated

5.0 FINISH:

- 5.1 Primer: Zinc-Chromate
- 5.2 Paint: Silver-Blue Enamel

6.0 APPROX. WEIGHT:

- 6.1 Net: 300 Lbs.
- 6.2 Shipping: 366 Lbs

Revision Letter	Date	Revision Description
ENGINEER		M.T.E.
APPROVED BY		April 20, 1998