FREQUENCY CONVERTER SPECIFICATION
GEORATOR CORPORATION

MANASSAS, VIRGINIA 20110

Model No. 33-157

Type 22-A Vertical Frequency Converter

1.0 INPUT:

1.1 Motor, Rotor And Stator: Reliance, Frame 254T, Georator P/N 18-309; 7.5 HP, 3 Phase, 60 Hz, 208-220/440V, 1760 RPM (Nom.).
1.2 Input Current: 21.1/10.5 Amperes
1.3 Insulation: Class B
1.4 Max. Ambient Temperature: 40 Degrees C
1.5 Duty: Continuous

2.0 OUTPUT:

2.1 Rating: 5 KVA, 100% PF, 1 Phase, 400 Hz (Nom.), 460V (Nom.).
2.2 Output Voltage, No Load: 480V +/-5V
2.3 Output Frequency Tolerance: 420 Hz Maximum @ No Load To 410 Hz +-1% @ Full Load
2.4 Output Current: 10.8 Amperes
2.5 Insulation: Class B
2.6 Duty: Continuous
2.7 Max. Ambient Temperature: 40 Degrees C
2.8 Dielectric Strength, Winding To Frame: 1500V For 1 Minute

3.0 VIBRATION: Within 0.0015

4.0 BEARINGS: Shielded Life Time Lubricated Motor Bearings

5.0 FINISH:

5.1 Primer: Mod Alkyd Resin Red. Fed Std TT-P-664D.

5.2 Paint: Silver-Blue Enamel

6.0 APPROXIMATE WEIGHT:

6.1 Net: 245 Lbs.
6.2 Shipping: 300 Lbs.

Revision Letter	Date	Revision Description

ENGINEER	M.T.E.
APPROVED BY	April 20, 1998