



FREQUENCY CONVERTER SPECIFICATION
GEORATOR CORPORATION
MANASSAS, VIRGINIA 20110

Model No. 39-012

Type 33-A Vertical Frequency Converter & Back Iron Regulator

1.0 INPUT:

- 1.1 Motor: Reliance, Induction, Stator and Rotor, Frame Size 254T; 15 H.P., 3 Phase, 50 Hz, 200/346V, 6 Wire, 1450 RPM (Nom.); Georator P/N 18-598
- 1.2 Input Current: 48.3/28 Amperes
- 1.3 Insulation: Class B
- 1.4 Max. Ambient Temperature: 40C
- 1.5 Duty: Continuous

2.0 OUTPUT:

- 2.1 Rating: 8.7 KVA, .95 PF, 3 Phase, 400 Hz (Nom.), 115/200V or 115V (Nom.)
- 2.2 Output Voltage, No Load; AC Values Before Regulation & Rectification:
 - (A) Power Winding: Approx. 144 \pm 1V L-N
 - (B) Control Winding: Approx. 53 \pm 1V L-L
- 2.3 Output Frequency Tolerances: 400 Hz @ N.L. To 388 Hz @ F.L.
- 2.4 Voltage Regulation: \pm 1.5% N.L. To F.L.
- 2.5 Voltage Adjustment: \pm 5%
- 2.6 Output Current Rating: 25.1/43.5 Amperes
- 2.7 Insulation: Class B
- 2.8 Max. Ambient Temperature: 40C
- 2.9 Dielectric Strength, Winding To Frame: 1500V For 1 Min.

3.0 VIBRATION: Within 0.0015

4.0 BEARINGS: Shielded Life Time Lubricated Motor Bearings

5.0 FINISH:

- 5.1 Primer: Modified Alkyd Resin Red fed std TT-P664D
- 5.2 Paint: Silver-Blue Enamel

6.0 APPROX. WEIGHT:

- 6.1 Net: 360 Lbs.
- 6.2 Shipping: 430 Lbs.

Revision Letter	Date	Revision Description
ENGINEER	M.T.E.	
APPROVED BY		April 20, 1998